

National Aeronautics and
Space Administration

John F. Kennedy Space Center



SPACEPORT
ENGINEERING AND
TECHNOLOGY

EXTREME VELOCITY WIND SENSOR

Jose M Perotti
Instrumentation Branch
Spaceport Engineering & Technology Directorate
Kennedy Space Center, Florida



Why A Hurricane Wind Sensor?

SPACEPORT
ENGINEERING AND
TECHNOLOGY

- **Kennedy Space Center (KSC) has the need to assess the mechanical stresses induced by high winds in their building and launch and landing structures.**
- **Most buildings and support structures were fabricated prior or during the Apollo Program era.**
- **If a hurricane hits KSC, there is a need to verify safety factors of buildings and support structures have not been exceeded.**

Why Another Hurricane Wind Sensor?




SPACEPORT
ENGINEERING AND
TECHNOLOGY

- **Current wind sensors used at KSC lack in two main areas:**
 - **Rotating cup or vane type anemometers have a high maintainability due to the wear-and-tear of their moving components.**
 - **There is a high degree of failure associated with such systems due to damage from extreme wind conditions.**
- **Experience developed from Hurricane Andrew (1992) demonstrated that existing wind sensing instrumentation would not withstand extreme hurricane winds.**



Why Another Hurricane Wind Sensor?

John F. Kennedy Space Center



National Aeronautics and
Space Administration

John F. Kennedy Space Center

Why Another Hurricane Wind Sensor?



National Aeronautics and
Space Administration


John F. Kennedy Space Center

SPACEPORT
ENGINEERING AND
TECHNOLOGY

Why Another Hurricane Wind Sensor?



- **Kennedy Space Center (KSC) also has the potential of being subjected to high winds produced by other than hurricanes.**
- **Strong thunderstorms, small tornadoes and water spouts are normally encountered during the summer.**



Our Hurricane Wind Sensor



Project Objectives

- **Provide KSC with a wind sensor with the following characteristics:**
 - rugged,
 - low profile,
 - highly reliable,
 - self-contained system for wind speed and direction,
 - Capable to measure wind speeds up to 300 mph, wind direction (in 45 degree increments) as well as temperature and RH.
- **Provide KSC with a wind sensor design that has no moving parts to reduce operation and maintenance costs.**

Our Hurricane Wind Sensor



Conceptual Design

- **The Extreme Velocity Wind Sensor is a device for the measurement of wind speed through the use of pressure measurements across a known shape.**
- **Form is a typical streamlined Venturi profile (a double-inflection curve) revolved 360 degrees about an axis passing vertically through the center of the profile.**
- **The profile has a series of instrumented ports located near the center and periphery to allow for pressure measurements along the surface.**
- **The wind speed is calculated from applying Bernoulli's law to the pressure change created between the ports. (Eqn. $P = \frac{1}{2} \rho * k * V^2$).**

Our Hurricane Wind Sensor



Conceptual Design

- **Wind direction is derived from the pressure profile distributed over the surface. Additionally, temperature and relative humidity measurements are incorporated into the design.**
- **Project involved the use of multi-discipline sensor technology combined with the development of smart embedded software algorithms.**
- **Project also incorporated the knowledge developed using Computational Fluid Dynamics (CFD) simulation of the design.**



National Aeronautics and
Space Administration

John F. Kennedy Space Center



Our Hurricane Wind Sensor

**SPACEPORT
ENGINEERING AND
TECHNOLOGY**



CFD Simulations of design



National Aeronautics and
Space Administration

Our Hurricane Wind Sensor



John F. Kennedy Space Center

SPACEPORT
ENGINEERING AND
TECHNOLOGY



CFD Simulations of design

Our Hurricane Wind Sensor



Project Present Status

- A Extreme Velocity Wind Sensor has been designed, developed, fabricated and is being tested at the present time.**
- Sensor has been modeled and computer simulation has been performed using CFD software.**
- Self-contained electronics has been conceptually designed. Analog section of design has been prototyped and initial testing performed.**
- Testing of sensor at Embry Riddle Aeronautical University (ERAU) is scheduled for later this year.**


National Aeronautics and
Space Administration

John F. Kennedy Space Center




**SPACEPORT
ENGINEERING AND
TECHNOLOGY**

Wind Speed Sensor Module



Wind Direction Sensor Module




Our Hurricane Wind Sensor



John F. Kennedy Space Center

SPACEPORT
ENGINEERING AND
TECHNOLOGY



Preliminary testing at ERAU



Our Hurricane Wind Sensor

SPACEPORT
ENGINEERING AND
TECHNOLOGY

Project Next Steps

- **Validate design at extreme wind velocities to 300 mph.**
- **Integrate methodology for wind direction determination.**
- **Optimize port locations to achieve best sensitivity and dynamic response.**
- **Optimize design to provide remote, standalone system capable of autonomously acquiring, recording, and storing storm information.**
- **Ruggedize the design for field deployment.**
- **Field deploy and test system.**